RoseDowns

ST**100** R Rendering PRESS





RoseDowns is a proud part of the global Desmet organisation

The innovative design of the ST100R Screw Press is a result of RoseDowns industry experience and knowledge, which has been gained over many years as one of the world leaders in the field of Oils and Fats.

ST100R Rendering press

Design Basis

- High Reliability
- Maintenance Friendly
- Flexible Layout & Installation
- Value Added Options

Key Features

- Feeder Assembly
- Worm Assembly
- Gearbox & Thrust Assembly
- Discharge End Bearing
- Stainless Steel Covers



global solutions provider of presses & parts for oilseeds and rendering



Heavy Duty Frame Fully welded construction to eliminate movement at joints.



Access One piece cast cage opens to 180° for ease of maintenance access.





Feed End Drive The gearbox and thrust assembly are located at the cooler and cleaner end of the press.



Cake Breaker Designed to break the fresh cake in the discharge end of the press, minimising wear & power consumption.



ear n.



Cake

Enabling safe & easy

sampling of the cake.

Â

Multistage Worm Assembly Low foots & long wear life, lower power consumption.



Dimensions		Weight	Weight		Installed Power (Subject to application)	
Length	3,100 mm	Overall Press	5,500 kg	Main Motor	30 kW (40 HP)	
Frame Width	725 mm	Half Cage	1,000 kg	Horizontal Feeder	0.75-1.5 kW (1-2 HP)	
Max Width	1,100 mm	Worm Assy	800 kg	Vertical Feeder	1.5 kW (2 HP)	
Frame Height	1,350 mm	Gearbox	1,000 kg	Cake Breaker*	1.5 kW (2 HP)	
Inlet Height	1,675 mm			Barring Motor*	5.5 kW (7 HP)	
Cage Bore	200 mm			Gearbox Oil Cooler*	0.75-1.5 kW (1-2 HP)	

(*) Optional. All dimensions are approximate. We reserve the right to alter the specification at any time without prior notice.

DESIGN AND MANUFACTURE OF SCREW PRESSES



Cannon Street - Kingston Upon Hull HU2 OAD - United Kingdom Tel +44 (0)1482 329864 | E-mail sales@rosedowns.co.uk

Großer Weidenweg 3a - 27367 Ahausen/Eversen - Germany Tel +49 (0)4231-982 88 0



rosedowns.co.uk